

Claims

What is claimed is:

1. A method of generating a three-dimensional graphical model of a region located within a living body, comprising the steps of:

(a) generating a three-dimensional model of a region of interest;

(b) determining the three-dimensional location of a physical characteristic in the region of interest using at least one probe positioned within the living body;

(c) deforming the model to at least approximately incorporate the physical characteristic at the determined three-dimensional location; and

(d) displaying the model on a graphical display.

2. The method of claim 1 further including:
repeating steps (b) through (d) multiple times for different probe locations to increase the conformity of the model to the actual region of interest within the living body.

3. The method of claim 1 further including the step of
(e) determining the relative three-dimensional location of a medical device positioned in the region of interest in the living body and graphically representing the medical device superimposed on the model at the determined three-dimensional location.

4. The method of claim 3 wherein the medical device is the at least one probe.

5. The method of claim 3 wherein:
the medical device includes at least one mapping electrode;
step (e) includes determining the relative three-dimensional
location of the at least one mapping electrode; and
5 the method further includes the steps of:
(f) detecting electrical activity using the at least one mapping
electrode; and
(g) generating a map of the detected electrical activity and
superimposing the map on the model at a three-dimensional location
10 corresponding to the determined three-dimensional location of the
electrode.

6. The method of claim 3 wherein:
the medical device includes at least one ablation electrode;
step (e) includes determining the relative three-dimensional
15 location of the at least one ablation electrode; and
the method further includes the steps of:
(f) forming a lesion using the at least one ablation electrode;
and
(g) generating a visual representation of the lesion and
20 superimposing the visual representation on the model at a three-
dimensional location corresponding to the determined three-
dimensional location of the electrode.

7. The method of claim 1 wherein the model generated in
step (a) includes anatomical features known to exist in the actual
25 region of interest, wherein the physical characteristics include
anatomical features, and wherein step (c) includes deforming the
model to correlate at least a portion of the anatomical features on

PATENT APPLICATION

Express Mailing Label: **EM503277091US**

the model with the determined three-dimensional locations of corresponding anatomical features in the living body.

8. The method of claim 7 wherein step (c) includes scaling the model to correlate at least a portion of the anatomical features on the model with the determined three-dimensional locations of corresponding anatomical features in the living body.

9. The method of claim 7 wherein step (c) includes orienting the model to correlate at least a portion of the anatomical features of the model with the determined three-dimensional locations of the corresponding anatomical features in the living body.

10. The method of claim 7 wherein step (c) includes performing a rigid body transformation.

11. The method of claim 10 wherein the rigid body transformation uses a procrustean algorithm.

12. The method of claim 1 wherein step (c) includes performing vector field interpolation on the model.

13. The method of claim 1 wherein the region of interest is an organ.

14. The method of claim 13 wherein the organ is a heart.

15. A method of generating a three-dimensional graphical model of an organ located within a living body, comprising the steps of

5 (a) generating a three-dimensional model of at least a portion of an organ, the model including a plurality of anatomical features corresponding to anatomical features in the organ;

(b) obtaining the relative three-dimensional locations of known anatomical features in the organ using a reference probe positioned in the organ;

10 (c) deforming the model using the determined relative three-dimensional locations of the anatomical features in the organ to approximately correlate the three-dimensional locations of the anatomical features on the model to the determined locations of corresponding anatomical features in the organ; and

15 (d) graphically displaying the model.

16. The method of claim 15 further including the steps of:

(e) obtaining the relative three-dimensional location of an additional physical characteristic in the organ using at least one probe positioned in the organ; and

20 (f) further deforming the model to approximately incorporate at least a portion of the additional physical characteristic.

17. The method of claim 16 further including repeating steps (e) and (f) multiple times for different probe locations to increase the conformity of the model to the organ.

5

10

15

20

CRDP-2700 [CPC2000.004]

Parameter	Control		Fertilizer		Fertilizer + PGR	
	Mean	SE	Mean	SE	Mean	SE
Plant height (cm)	10.5	0.5	10.5	0.5	10.5	0.5
Stem diameter (mm)	1.5	0.1	1.5	0.1	1.5	0.1
Root length (cm)	15.0	1.0	15.0	1.0	15.0	1.0
Root diameter (mm)	2.0	0.2	2.0	0.2	2.0	0.2
Shoot weight (g)	1.0	0.1	1.0	0.1	1.0	0.1
Root weight (g)	0.5	0.05	0.5	0.05	0.5	0.05
Chlorophyll content (SPAD)	25.0	1.0	25.0	1.0	25.0	1.0
Stomatal conductance (mmol m ⁻² s ⁻¹)	0.1	0.01	0.1	0.01	0.1	0.01
Transpiration rate (mmol m ⁻² s ⁻¹)	0.05	0.005	0.05	0.005	0.05	0.005
Water use efficiency (g g ⁻¹)	2.0	0.2	2.0	0.2	2.0	0.2
Relative water content (%)	80.0	2.0	80.0	2.0	80.0	2.0
Protein content (%)	10.0	0.5	10.0	0.5	10.0	0.5
Carbohydrate content (%)	5.0	0.2	5.0	0.2	5.0	0.2
Antioxidant activity (U g ⁻¹)	1.0	0.1	1.0	0.1	1.0	0.1
Chlorophyll fluorescence (Fv/Fm)	0.8	0.05	0.8	0.05	0.8	0.05
Stomatal conductance (mmol m ⁻² s ⁻¹)	0.1	0.01	0.1	0.01	0.1	0.01
Transpiration rate (mmol m ⁻² s ⁻¹)	0.05	0.005	0.05	0.005	0.05	0.005
Water use efficiency (g g ⁻¹)	2.0	0.2	2.0	0.2	2.0	0.2
Relative water content (%)	80.0	2.0	80.0	2.0	80.0	2.0
Protein content (%)	10.0	0.5	10.0	0.5	10.0	0.5
Carbohydrate content (%)	5.0	0.2	5.0	0.2	5.0	0.2
Antioxidant activity (U g ⁻¹)	1.0	0.1	1.0	0.1	1.0	0.1
Chlorophyll fluorescence (Fv/Fm)	0.8	0.05	0.8	0.05	0.8	0.05

(h) deriving the relative three-dimensional locations of an additional physical characteristic in the organ using the determined three-dimensional locations of the ultrasonic transducers; and

(i) further deforming the model to approximately incorporate at least a portion of the additional physical characteristic.

23. A method of generating a three-dimensional graphical model of a heart located within a living body, comprising the steps of:

(a) generating a three-dimensional model of the heart, the model including a plurality of anatomical features corresponding to known anatomical features of hearts;

(b) obtaining the relative three-dimensional locations of known anatomical features in the heart using a reference catheter positioned in the heart;

(c) deforming the model using the determined relative three-dimensional locations of the anatomical features in the organ to approximately correlate the three-dimensional locations of the anatomical features on the model to the determined locations of corresponding anatomical features in the heart;

(d) positioning an additional probe in a chamber of the heart;

(e) obtaining the relative three-dimensional location of a physical characteristic in the chamber using the additional probe;

(f) further deforming the model to approximately incorporate at least a portion of the physical characteristic; and

(g) graphically displaying the model.

PATENT APPLICATION

Expr ss Mailing Label: EM503277091US

24. The method of claim 23 further comprising the step of repositioning the additional probe and repeating steps (e) and (f) multiple times to increase the conformity of the model to the heart.

25. The method of claim 23 further including the steps of:
(h) providing a medical device having at least one electrode;
(i) positioning the medical device in the chamber; and
(j) determining the relative three-dimensional location of the at least one electrode and graphically representing the electrode superimposed on the model at the determined three-dimensional location.

26. The method of claim 25 wherein the medical device is the at least one probe.

27. The method of claim 23 further comprising the steps of:
(h) providing a medical device having at least one mapping electrode;
(i) positioning the medical device in the chamber;
(j) determining the relative three-dimensional location of the at least one mapping electrode
(k) detecting electrical activity using the at least one mapping electrode; and
(l) generating a map of the detected electrical activity and superimposing the map on the model at a three-dimensional location corresponding to the determined three-dimensional location of the electrode.

28. The method of claim 27 wherein the medical device includes a plurality of mapping electrodes, wherein steps (j) through (l) are carried out using the plurality of mapping electrodes, and wherein the map generated in step (l) is an isochronal map.

5 29. The method of claim 27 wherein the medical device includes a plurality of mapping electrodes, wherein steps (j) through (l) are carried out using the plurality of mapping electrodes, and wherein the map generated in step (l) is an isopotential map.

10 30. The method of claim 23 further including the steps of:
(h) providing a medical device having at least one ablation electrode;
(i) positioning the medical device in the chamber;
(j) determining the relative three-dimensional location of the at least one ablation electrode;
15 (k) forming a lesion using the at least one ablation electrode; and
(l) generating a visual representation of the lesion and superimposing the visual representation on the model at a three-dimensional location corresponding to the determined three-
20 dimensional location of the electrode.

31. A system for generating a three-dimensional graphical model of a region located within a living body, comprising:
a graphical display;
display software for generating a model of a region of interest
25 and for displaying the model on the graphical display;

09128304 080398
35E030 40E02160

a probe positionable with a region in a living body
corresponding to the region of interest;

a localization system for determining the three-dimensional
location of at least a portion of the probe when the probe is
positioned in a living body, and for deriving the three-dimensional
location of a physical characteristic in the region of interest from the
determined three-dimensional location of the probe; and

transformation software for deforming the model to at least
approximately incorporate the physical characteristic at the
determined three-dimensional location.

32. The system of claim 31 wherein:

the system further includes a medical device positionable in
the region of interest;

the localization system is further for determining the relative
three-dimensional location of the medical device when it is
positioned in the region of interest in the living body; and

the display software is further for graphically representing the
medical device superimposed on the model at the determined three-
dimensional location.

33. The system of claim 32 wherein:

the medical device includes at least one electrode;

the localization system is further for determining the relative
three-dimensional location of the electrode when it is positioned in
the region of interest in the living body; and

the display software is for graphically representing the
electrode superimposed on the model at the determined three-
dimensional location.

34. The system of claim 32 wherein:

the medical device includes at least one mapping electrode;

the localization system is further for determining the relative
three-dimensional location of the mapping electrode when it is
positioned in the region of interest in the living body;

the system further includes an electrophysiology system for
receiving detected electrical activity from the mapping electrode and
for generating a map of the electrical activity; and

the display software is for graphically representing the map
superimposed on the model at the three-dimensional location
corresponding to the three-dimensional location of the electrode.

35. The system of claim 32 wherein:

the medical device includes at least one ablation electrode;

the localization system is further for determining the relative
three-dimensional location of the ablation electrode when it is
positioned in the region of interest in the living body;

the system further includes an ablation system for delivering
ablation energy to the ablation electrode; and

the display software is for generating a visual representation
of an ablation lesion and for superimposing the visual representation
of the lesion on the model at a three-dimensional location
corresponding to the three-dimensional location of the electrode.

36. The system of claim 31 wherein the display software is
for generating and displaying a model of an organ.

37. The system of claim 36 wherein the organ is a heart.

38. A system for generating a three-dimensional graphical model of an organ located within a living body, comprising:

a graphical display;

display software for generating a model of an organ and for displaying the model on the graphical display, the model including a plurality of anatomical features corresponding to anatomical features in the organ;

a reference probe positionable within or in proximity to an organ in a living body;

a localization system for determining the three-dimensional location of at least a portion of the reference probe when the probe is positioned within or in proximity to the organ, and for deriving the three-dimensional locations of anatomical features in the organ from the determined three-dimensional location of the reference probe; and

transformation software for deforming the model to at least approximately correlate the three-dimensional locations of the anatomical features on the model to the determined locations of corresponding anatomical features in the organ.

39. The system of claim 38 wherein:

the system further comprises an additional probe positionable within or in proximity to the organ;

the localization system is further for obtaining the relative three-dimensional location of at least a portion of the additional probe and for deriving the three-dimensional location of an additional physical characteristic of the organ from the three-dimensional location of the additional probe; and

PATENT APPLICATION

Express Mailing Label: **EM503277091US**

the transformation software is further for deforming the model to approximately incorporate at least a portion of the additional physical characteristic.

40. The system of claim 39 wherein:

the probe is moveable to multiple locations within the organ;

the localization system is further for deriving the locations of multiple physical characteristics within the organ from each of the multiple locations of the additional probe; and

the transformation software is further for deforming the model to approximately incorporate the multiple physical characteristics to increase the conformity between the model and the organ.

41. The system of claim 38 wherein the organ is a heart.

42. The system of claim 41 wherein:

the system further includes a medical device positionable in the heart;

the localization system is further for determining the relative three-dimensional location of the medical device when it is positioned in the heart; and

the display software is further for graphically representing at least a portion the medical device superimposed on the model at the determined three-dimensional location.

43. The system of claim 42 wherein:

the medical device includes at least one electrode;

PATENT APPLICATION

Express Mailing Label: EM503277091US

the localization system is further for determining the relative three-dimensional location of the at least one electrode when it is positioned in the heart; and

5 the display software is for graphically representing the electrode superimposed on the model at the determined three-dimensional location.

44. The system of claim 42 wherein
the medical device includes at least one mapping electrode;
the localization system is further for determining the relative
10 three-dimensional location of the at least one mapping electrode when it is positioned in the heart;

the system further includes an electrophysiology system for receiving detected electrical activity from the mapping electrode and for generating a map of electrical activity within the heart; and

15 the display software is further for superimposing the map on the model at a three-dimensional location corresponding to the three-dimensional location of the electrode.

45. The system of claim 42 wherein:
the medical device includes at least one ablation electrode;
20 the localization system is further for determining the relative three-dimensional location of the at least one ablation electrode when it is positioned in the heart;

the system further includes an ablation system for delivering ablation energy to the ablation electrode to create a lesion in the
25 heart; and

the display software is further for generating a visual representation of an ablation lesion and for superimposing the visual

PATENT APPLICATION

Express Mailing Label: EM503277091US

representation on the model at a three-dimensional location corresponding to the three-dimensional location of the electrode.

5 46. The system of claim 44 wherein the medical device includes a plurality of mapping electrodes, wherein the electrophysiology system is for generating an isochronal map, and wherein the display software is for superimposing the map on the model.

10 47. The system of claim 44 wherein the medical device includes a plurality of mapping electrodes, wherein the electrophysiology system is for generating an isopotential map, and wherein the display software is for superimposing the map on the model.

15 *Sub*
an 48. A method of graphically displaying and dynamically correcting an image of organ comprising the steps of:
generating a graphical image of the organ;
inserting a catheter into the body and obtaining data corresponding to the location of a physical characteristic associated with the organ;
20 modifying the graphical image with the location data;
and
displaying the modified graphical image.

49. A method as recited in claim 48 wherein the physical characteristic is an anatomical feature.

PATENT APPLICATION

Express Mailing Label: EM503277091US

50. A method as recited in claim 48 wherein the physical characteristic is an interior point.

51. A method as recited in claim 48 wherein the physical characteristic is an interior point.

5 Sub
A2) 52. A method as recited in claim 48 further include the step of repositioning the catheter multiple times and repeating the obtaining, modifying and displaying steps for each catheter position.

10 53. A method as recited in claim 48 further including the step of obtaining a fluoroscopic image of the catheter and its position with respect to the organ and modifying the graphical image with the fluoroscopic position information.

15 54. A method as recited in claim 48 further including the step of obtaining input specifying the physical characteristic associated with the organ and modifying the graphical image with the input.

20 55. A method as recited in claim 48 wherein the method further comprises the steps of positioning a plurality of ultrasonic transducers into the body, at least one of the ultrasonic transducers being on the catheter, and wherein the obtaining step includes the steps of:

causing the transducers to generate and/or receive ultrasound signals and recording the elapsed time between the generation of signals from each transmitting one of the

PATENT APPLICATION

Express Mailing Label: EM503277091US

transducers and the receipt of the signals by receiving ones of the transducers;

determining the three-dimensional location of the catheter based on the recorded times; and

5 deriving the location of the physical characteristic from the determined location of the catheter.

Sub
a3

56. A system for graphically displaying and dynamically correcting an image of organ comprising:

10 a processor for generating an image of an organ;
a display for displaying the generated image;
a catheter for placement into the body adjacent the organ; and

15 means associated with the catheter for generating data related to the position of the catheter and wherein said processor utilizes said position data to update the image of the organ.

20 57. A system as recited in claim 56 further including means for obtaining a fluoroscopic image of the organ and the catheter further including a means for inputting information related to the location of the catheter obtained from the fluoroscopic image into the processor to further update the image of the organ.

25 58. A system as recited in claim 56 wherein the system further includes a plurality of ultrasonic transducers positionable within the living body, at least one of the transducers being on the catheter, and wherein the means associated with the catheter includes:

09128304-080398

PATENT APPLICATION

Express Mailing Lab I: EM503277091US

5 localization hardware electronically coupled to the transducers
for causing the ultrasound transducers to transmit and/or receive
ultrasound signals and for measuring the elapsed time between
transmission of ultrasound signals by transmitting transducers and
receipt of the signals by receiving transducers;

10 processor means electronically coupled to the localization
hardware for calculating the distances between the transducers
using the measured elapsed time, for determining the three-
dimensional location of the catheter, and for deriving the location of
the organ from the three dimensional location of the catheter.

And B47

0913340932160